



## **SLEEKWRAPPER 55BB SERVO STAINLESS STEEL HORIZONTAL FLOWPACK**



### **Benefits and Advantages**

The state of the art high speed SleekWrapper 55BB servo driven horizontal wrapping machine offers an excellent price/value ratio as well as a low cost of ownership and maintenance. Manufactured using in most part 304 stainless steel and well-known brand componentry for “off the shelf” availability anywhere in the world.

The SleekWrapper 55BB uses servo motors and servo drives that creates quick and easy changeover and adjustment. Servo drives assures precise positioning, smooth acceleration – deceleration and very little cause or need for maintenance. The simple design makes the Sleek flow wrapper very easy to set-up, operate, and maintain.

Equipped with a dual lug position infeed conveyor and forming shoulder; changing product is very simple without the headache and cost of changing parts.



## **SLEEKWRAPPER 55BB SERVO STAINLESS STEEL HORIZONTAL FLOWPACK**

### Features

- Left to Right product flow
- Welded stainless steel frame
- Infeed conveyor includes plastic holders and snap-on pushers
- Photo Cell for Bag Registration
- Cantilevered single film holder
- Color touch screen HMI and Mitsubishi PLC
- Auto open / close rotary fin wheel assembly
- PID temperature control
- Pre-programmed and stored product set-up
- Rotary seal jaws with jam detecting logic

### Specifications

#### Maximum Web Width

- 19" (500 mm)

#### Package Width

- 1" – 7.5" (25 mm - 200 mm)

#### Package Length

- Up to 22" (550 mm)

#### Maximum Package Height

- Up to 3.75" (100 mm)\*  
subject to web width

#### Max film roll diameter

- 13" (350 mm)  
With 3" (80 mm) core

#### Maximum Mechanical Rate

- Up to 100 cycles per minute subject to package size.

**480V 3 Phase, 25 A, 90PSI**