

Bingo bagger

XL



Benefits and Advantages

- The Bingo Bagger XL is designed for big bag applications for up to 50 lbs. (22 kg) of product.
- Stainless steel construction using 304 S/S, standard food grade for all contact parts.
- Uses pre-made wicketed bags, will automatically open, fill, and seal.
- Both polyethylene and laminate materials can be run on the Bingo Bagger XL.
- Wide bag size specs versatility.
- PLC operated top loading horizontal bagger is compact, mobile and very user friendly.
- The Bingo Bagger XL uses horizontal seal jaws as opposed to a traditional rotary heat sealer, this not only reduces the length of the machine but cost as well.

Bingo bagger

XL



Vacuum feature available



Uses wicketed bags

Features

- Stationary product funnel
- Right to Left Bag Discharge
- Exair amplifier on adjustable pivot
- Linear rod-less cylinder on roller bearing rack
- Rotary pneumatic cylinders for finger rotation
- Bag support table
- Menu driven controls with memory storage
- Stationary bag seal station
- Independent pneumatic knife assembly
- Bag trim removal mechanism
- Digital temperature control

Specifications

Electrical

- North American 230 VAC / 1 Ph / 60 Hz
- International 240 VAC / 1 Ph / 50 Hz
- All other electrical specifications available on request at additional cost

Air

- North American 12 CFM / 90 PSI
- International 360 L / min / 6 bar

Bag Widths

- 14 to 20 inches (355 - 508 mm)

Bag Lengths

- 14 to 24 inches (355 - 609 mm)