

# DOMINATOR"

14

**PRE-GRINDER** 



A high-volume grinder designed with advanced innovative features able to deliver higher productivity as well as improved product texture. Designed specifically for fresh meat pre-grind applications.

Note: Safety labels removed for clarity.
All guards and labels must be in place while operating.

- Engineered to provide a Balanced Flow of product.
  - Improved product texture
  - More consistent particle definition and dimension
  - Higher productivity
  - Improved hard tissue and bone removal
- User friendly assembly and disassembly.
- Reduced operating costs.
- Increased life expectancy of gearbox and feedscrew splines.

### **DOMINATOR™ 14**

#### **SPECIFICATIONS:**

• **DRIVE**: 100 HP (75 kw).

CONSTRUCTION: 304 stainless steel, except for ring (tinned).

• **SCREW**: 9" (229 mm) diameter.

• KNIFEHOLDER: 3 or 6 blade available.

• WEIGHT (Approx.): Unskidded: 4981 lbs. (2259 kg); Skidded: 5251 lbs. (2382 kg).


• GRINDER PLATE SIZE: 14" (356 mm) diameter. Plate hole sizes available from

1/4" (6 mm) to 2" (50 mm) and larger.

• GRIND RATE\*: Pre-grind: 1,800 - 2,000 lbs./min. (816 - 907 kg./min.)

108,000 - 120,000 lbs./hr. (48,960 - 54,420 kg./hr.)

#### **DIMENSIONS:**



Α	В	С	D	E	F	G *	H *	1*	J*	K*	L*	M	N	0
170	24	38	32	38	30	39	42	48	83	68	37	38	32	41
(4318)	(610)	(965)	(813)	(965)	(762)	(991)	(1067)	(1219)	(2108)	(1727)	(940)	(965)	(813)	(1041)

Dimensions shown are rounded in inches (mm).

\* Up to 3" (76 mm) height adjustment.

Dimensions and specifications subject to change without notice.

Note: Dimensions shown should not be used for installation purposes. Please request a certified approval drawing from Weiler.

## WEILER® and Company, Inc.

www.weilerinc.com email: sales@weilerinc.com Corporate Headquarters: Whitewater, Wisconsin U.S.A.

USA: 262-473-5254 • 800-558-9507 • Fax: 262-473-5867 • Europe: +44 (0) 1454 320900 • Fax: +44 (0) 1454 326262

Grinders • Mixers • Conveyors • Mixer Grinders • Separators • Complete Systems

<sup>\*</sup> Actual grind rate will depend on plate hole size, raw material, temperature, and feeding method.